

SPECIFICATION
REDDICK THREE POINT HITCH SRAYER
MODEL: S5P-300-16

DESCRIPTION: Stock Number: S5P300 - Reddick s5 3pt Mount 300 Gallon 16 Row Sprayer, 15" Spacing, 40' Boom, 5 Section Auto Rate Control, Hydraulic Pump, Triple Nozzle Bodies w/8003 tips, Foam Markers, Rinse Tank , Rear Step

STANDARARD FEATURES & SPECS:

- Heavy-Duty Tubular boxed Frame Fits Category II or III 3 point hitch frame Quick Hitch
- 300 gallon polyethylene tank
- Hydro 9006C-0 PTO centrifugal pump. 540 RPM
- Hydraulic Cylinders for Boom Fold
- Hydraulic Front Folding Booms with shock absorbers
- Formed Beak-A-Way Boom Hinges
- Bridged Boom Arms. Three Pieces of Square Tubing Trussed
- QJ300 Quick-Jet No-Drip Nozzle Bodies w/Diaphragm Checks
- 1-1/2" Fill Kit: Includes Ball Valve & Camlock Coupler
- VisFlo Tips Color Coded Hollow-Cone Nozzles
- Stiff Arm Connecting Boom Arm to Back Frame
- 3" Square Tubular Back Frame
- High Volume In-Line Strainer
- 10 gallon Richway foam marker
- 5 gallon fresh water hand wash tank
- Hydraulic driven pump
- Rear step for easy access to top of tank
- Flow meter, regulating valve and high capacity strainer
- Ground speed supplied by JD CAN on tractor
- IC18 Sprayer Module with all necessary wiring harnesses
- Switchbox to operate valves (Easier than using display)
- One set of 8003VS spray tips with caps and strainers included5 section manifold with 5 boom shut off valves
- 33 diaphragm check triple nozzle bodies on 15 inch spacing